

English “Drip Bar” Locks, right or left #Lock-LR-500 or 600

The English “bar” lock is so-called because it uses a “drip bar” soldered to the barrel, instead of wood above the lock plate. This improvement eliminates wood in this critical area ahead of the nipple, where constant over-spray might char it, or oil from the bore might soak it.

Most better London & Birmingham makers used “bar” locks, as did such famous American makers as H. E. Dimick of St. Louis. The bar lock was used on half stock rifles. When used in pairs on double guns, barrels overhang the plates, to eliminate the filler bars.

We offer the right drip bar only. Matching right and left bars can be made from two right bars.

Other features include a fly, and mainspring link with integral pins, which pivots to lift out of the tumbler, a fine English feature. The hammer has a long 1.745” throw for use with barrels from 15/16” up to 1-1/4” at breech. Our left “bar” locks exactly match our right locks. In lieu of a front bolt, a lug can be added inside the plate, to hook under a hidden wood screw head, set in the lock mortise.

Since the internal parts are used in other L&R locks, the other styles of hammers may be fitted to these locks. The Hawken, Leman, and English hammers are misnomers, as all these are really English designs. We use these names for clarity, since these hammer shapes are well known from those locks. Our matching hammers, locks and parts may be used to repair or replicate old rifles and shotguns.

- #Lock-LR-500 lock, early flat hammer, right **only \$92.00**
- #Lock-LR-600 lock, early flat hammer, left **only \$92.00**
- #Lock-LR-500-S lock, Express hammer, right **only \$92.00**
- #Lock-LR-600-S lock, Express hammer, left **only \$92.00**

©2012, Track of the Wolf, Inc.
shown actual size
 Made in the U.S.A.
 by L&R Lock Co.
left or right

Parts for English “Drip Bar” lock, left #Lock-LR-600

- #Lock-LR-600-PI left lock plate, 5.17 x 1.06”, cut for bar **\$25.50**
- #Lock-LR-600-Ha left flat faced hammer, 1.745” throw **\$13.50**
- #Lock-LR-100-Ha left, Express hammer, 1.745” throw **\$14.00**
- #Lock-LR-200-Ha left English hammer, 1.700” throw **\$13.50**
- #Lock-LR-100-Tu left tumbler, tapped 6-40, cut for fly **\$18.00**
- #Lock-LR-100-Tx left tumbler screw, 6-40 thread **\$ 2.49**
- #Lock-LR-100-FI fly detent, with hole for stud **\$ 2.50**
- #Lock-LR-200-Br left bridle, accepts three 6-40 screw **\$13.50**
- #Lock-LR-100-Bx bridle screw, 6-40 thread, use two **\$ 1.50**
- #Lock-LR-200-Se left sear tempered, use 6-40 screw **\$13.50**
- #Lock-LR-100-Sx sear screw, .600” long, 6-40 thread **\$ 1.50**
- #Lock-LR-200-Ss left sear spring, flat style, tempered **\$ 3.25**
- #Lock-LR-100-Ssx sear spring screw, 6-40 thread **\$ 1.50**
- #Lock-LR-200-Ms left mainspring, tempered **\$19.00**
- #Lock-LR-100-Li link and pin, short **\$ 6.99**

English Drip Bar Percussion Locks



#Lock-LR-500
 English drip bar lock
 with early
 flat face hammer
\$92.00

Concave face drip bar, for
 L&R's English bar lock.
#Lock-LR-Baronly \$7.59

Parts for English “drip bar” lock, right #Lock-LR-500

- #Lock-LR-500-PI lock plate, 5.17 x 1.06”, cut for bar **\$25.50**
- #Lock-LR-500-Ha flat faced hammer, 1.745” throw **\$13.50**
- #Lock-LR-100-Ha Express hammer, 1.745” throw **\$14.00**
- #Lock-LR-100-Tu tumbler, tapped 6-40, cut for fly **\$18.00**
- #Lock-LR-100-Tx tumbler screw, 6-40 thread **\$ 2.49**
- #Lock-LR-100-FI fly detent, with hole for stud **\$ 2.50**
- #Lock-LR-100-Br bridle, use three 6-40 screws **\$13.50**
- #Lock-LR-100-Bx bridle screw, 6-40 thread, use two **\$ 1.50**
- #Lock-LR-100-Se sear, tempered, use 6-40 screw **\$13.50**
- #Lock-LR-100-Sx sear screw, .60” long, 6-40 thread **\$ 1.50**
- #Lock-LR-100-Ss sear spring, flat style, tempered **\$ 3.25**
- #Lock-LR-100-Ssx sear spring screw, 6-40 thread **\$ 1.50**
- #Lock-LR-100-Ms mainspring, tempered **\$19.00**
- #Lock-LR-100-Li link with integral pins, tempered **\$ 6.99**

#Lock-LR-500-S
 English drip bar lock
 with Express hammer,
 right
\$92.00



**Elegant curved
 Express Rifle
 hammers,
 left or right**